

**Тусо Thermal Controls 2009 .**

| Item | Unit | Description  | price USD | Unit |
|------|------|--|-----------|------|
|      |      |  | DDP-07    |      |
| 1    | m    | <b>3BTV2-CT</b><br>Self-regulating strip heater              | 31,31     |      |
| 2    | m    | <b>5BTV2-CT</b><br>Self-regulating strip heater              | 34,50     |      |
| 3    | m    | <b>8BTV2-CT</b><br>Self-regulating strip heater              | 38,78     |      |
| 4    | m    | <b>10BTV2-CT</b><br>Self-regulating strip heater             | 42,50     |      |
| 5    | m    | <b>10QTVR2-CT</b><br>Self-regulating strip heater            | 56,03     |      |
| 6    | m    | <b>15QTVR2-CT</b><br>Self-regulating strip heater            | 62,38     |      |
| 7    | m    | <b>20QTVR2-CT</b><br>Self-regulating strip heater            | 69,41     |      |
| 8    | m    | <b>4XTV2-CT</b><br>Self-regulating strip heater              | 55,48     |      |
| 9    | m    | <b>8XTV2-CT</b><br>Self-regulating strip heater              | 59,20     |      |
| 10   | m    | <b>12XTV2-CT</b><br>Self-regulating strip heater             | 62,38     |      |
| 11   | m    | <b>15XTV2-CT</b><br>Self-regulating strip heater             | 66,79     |      |
| 12   | m    | <b>20XTV2-CT</b><br>Self-regulating strip heater             | 70,52     |      |
| 13   | m    | <b>5KTV2-CT</b><br>Self-regulating strip heater              | 95,36     |      |
| 14   | m    | <b>8KTV2-CT</b><br>Self-regulating strip heater              | 104,47    |      |
| 15   | m    | <b>15KTV2-CT</b><br>Self-regulating strip heater             | 112,06    |      |
| 16   | m    | <b>20KTV2-CT</b><br>Self-regulating strip heater             | 121,16    |      |
| 17   | m    | <b>5VPL2-CT</b><br>Selflimiting strip heater                 | 71,90     |      |
| 18   | m    | <b>10VPL2-CT</b><br>Selflimiting strip heater                | 77,69     |      |
| 19   | m    | <b>15VPL2-CT</b><br>Selflimiting strip heater                | 84,73     |      |
| 20   | m    | <b>20VPL2-CT</b><br>Selflimiting strip heater                | 91,22     |      |
| 21   | m    | <b>EM2-XR</b><br>Self-regulating strip heater                | 26,36     |      |
| 22   |      | <b>HDF1M160 - / length - 50</b><br>MI-element                | 0,00      |      |
| 23   | m    | <b>XPI-0.8 CL (EEx e II)</b><br>Cold Lead cable              | 46,52     |      |
| 24   | m    | <b>XPI-1.1 CL (EEx e II)</b><br>Cold Lead cable              | 37,40     |      |
| 25   | m    | <b>XPI-1.8 CL (EEx e II)</b><br>Cold Lead cable              | 32,71     |      |
| 26   | m    | <b>XPI-2.9 CL (EEx e II)</b><br>Cold Lead cable              | 26,08     |      |
| 27   | m    | <b>XPI-4.4 CL (EEx e II)</b><br>Cold Lead cable              | 20,56     |      |
| 28   | m    | <b>XPI-7 (EEx e II)</b><br>Constant wattage heating cable    | 15,87     |      |
| 29   | m    | <b>XPI-10 (EEx e II)</b><br>Constant wattage heating cable   | 13,25     |      |
| 30   | m    | <b>XPI-11.7 (EEx e II)</b><br>Constant wattage heating cable | 13,25     |      |
| 31   | m    | <b>XPI-15 (EEx e II)</b><br>Constant wattage heating cable   | 13,25     |      |
| 32   | m    | <b>XPI-17.8 (EEx e II)</b><br>Constant wattage heating cable | 12,42     |      |
| 33   | m    | <b>XPI-25 (EEx e II)</b><br>Constant wattage heating cable   | 12,01     |      |
| 34   | m    | <b>XPI-31.5 (EEx e II)</b><br>Constant wattage heating cable | 12,01     |      |
| 35   | m    | <b>XPI-50 (EEx e II)</b><br>Constant wattage heating cable   | 12,01     |      |

Tyco Thermal Controls 2009 .

| Item | Unit | Description  | price USD | Unit |
|------|------|--|-----------|------|
| 36   | m    | <b>XPI-65 (EEx e II)</b><br>Constant wattage heating cable   | 12,14     |      |
| 37   | m    | <b>XPI-80 (EEx e II)</b><br>Constant wattage heating cable   | 12,14     |      |
| 38   | m    | <b>XPI-100 (EEx e II)</b><br>Constant wattage heating cable  | 12,97     |      |
| 39   | m    | <b>XPI-150 (EEx e II)</b><br>Constant wattage heating cable  | 12,70     |      |
| 40   | m    | <b>XPI-180 (EEx e II)</b><br>Constant wattage heating cable  | 12,70     |      |
| 41   | m    | <b>XPI-200 (EEx e II)</b><br>Constant wattage heating cable  | 12,70     |      |
| 42   | m    | <b>XPI-320 (EEx e II)</b><br>Constant wattage heating cable  | 12,70     |      |
| 43   | m    | <b>XPI-380 (EEx e II)</b><br>Constant wattage heating cable  | 12,56     |      |
| 44   | m    | <b>XPI-480 (EEx e II)</b><br>Constant wattage heating cable  | 12,56     |      |
| 45   | m    | <b>XPI-600 (EEx e II)</b><br>Constant wattage heating cable  | 12,56     |      |
| 46   | m    | <b>XPI-700 (EEx e II)</b><br>Constant wattage heating cable  | 12,56     |      |
| 47   | m    | <b>XPI-810 (EEx e II)</b><br>Constant wattage heating cable  | 11,45     |      |
| 48   | m    | <b>XPI-1000 (EEx e II)</b><br>Constant wattage heating cable | 11,45     |      |
| 49   | m    | <b>XPI-1440 (EEx e II)</b><br>Constant wattage heating cable | 11,45     |      |
| 50   | m    | <b>XPI-1750 (EEx e II)</b><br>Constant wattage heating cable | 11,45     |      |
| 51   | m    | <b>XPI-2000 (EEx e II)</b><br>Constant wattage heating cable | 11,45     |      |
| 52   | m    | <b>XPI-3000 (EEx e II)</b><br>Constant wattage heating cable | 11,04     |      |
| 53   | m    | <b>XPI-4000 (EEx e II)</b><br>Constant wattage heating cable | 10,76     |      |
| 54   | m    | <b>XPI-4400 (EEx e II)</b><br>Constant wattage heating cable | 10,76     |      |
| 55   | m    | <b>XPI-5160 (EEx e II)</b><br>Constant wattage heating cable | 10,76     |      |
| 56   | m    | <b>XPI-5600 (EEx e II)</b><br>Constant wattage heating cable | 10,76     |      |
| 57   | m    | <b>XPI-7000 (EEx e II)</b><br>Constant wattage heating cable | 10,76     |      |
| 58   | m    | <b>XPI-8000 (EEx e II)</b><br>Constant wattage heating cable | 10,76     |      |
| 59   | m    | <b>XPI-NH-0.8</b><br>Constant wattage heating cable          | 42,92     |      |
| 60   | m    | <b>XPI-NH-1.1</b><br>Constant wattage heating cable          | 34,09     |      |
| 61   | m    | <b>XPI-NH-1.8</b><br>Constant wattage heating cable          | 25,39     |      |
| 62   | m    | <b>XPI-NH-2.9</b><br>Constant wattage heating cable          | 18,49     |      |
| 63   | m    | <b>XPI-NH-4.4</b><br>Constant wattage heating cable          | 14,77     |      |
| 64   | m    | <b>XPI-NH-7</b><br>Constant wattage heating cable            | 10,35     |      |
| 65   | m    | <b>XPI-NH-10</b><br>Constant wattage heating cable           | 8,28      |      |
| 66   | m    | <b>XPI-NH-11.7</b><br>Constant wattage heating cable         | 8,28      |      |
| 67   | m    | <b>XPI-NH-15</b><br>Constant wattage heating cable           | 8,28      |      |
| 68   | m    | <b>XPI-NH-17.8</b><br>Constant wattage heating cable         | 8,28      |      |
| 69   | m    | <b>XPI-NH-25</b><br>Constant wattage heating cable           | 7,87      |      |
| 70   | m    | <b>XPI-NH-31.5</b><br>Constant wattage heating cable         | 7,87      |      |
| 71   | m    | <b>XPI-NH-50</b><br>Constant wattage heating cable           | 7,87      |      |
| 72   | m    | <b>XPI-NH-65</b><br>Constant wattage heating cable           | 7,87      |      |
| 73   | m    | <b>XPI-NH-80</b><br>Constant wattage heating cable           | 7,87      |      |

Tyco Thermal Controls 2009 .

| Item | Unit      | Description  | price USD | Unit |
|------|-----------|--|-----------|------|
| 74   | m         | <b>XPI-NH-100</b><br>Constant wattage heating cable                      | 8,14      |      |
| 75   | m         | <b>XPI-NH-150</b><br>Constant wattage heating cable                      | 7,87      |      |
| 76   | m         | <b>XPI-NH-180</b><br>Constant wattage heating cable                      | 7,87      |      |
| 77   | m         | <b>XPI-NH-200</b><br>Constant wattage heating cable                      | 7,87      |      |
| 78   | m         | <b>XPI-NH-320</b><br>Constant wattage heating cable                      | 7,87      |      |
| 79   | m         | <b>XPI-NH-380</b><br>Constant wattage heating cable                      | 7,87      |      |
| 80   | m         | <b>XPI-NH-480</b><br>Constant wattage heating cable                      | 7,87      |      |
| 81   | m         | <b>XPI-NH-600</b><br>Constant wattage heating cable                      | 7,59      |      |
| 82   | m         | <b>XPI-NH-700</b><br>Constant wattage heating cable                      | 7,59      |      |
| 83   | m         | <b>XPI-NH-810</b><br>Constant wattage heating cable                      | 7,59      |      |
| 84   | m         | <b>XPI-NH-1000</b><br>Constant wattage heating cable                     | 7,18      |      |
| 85   | m         | <b>XPI-NH-1440</b><br>Constant wattage heating cable                     | 7,18      |      |
| 86   |           | <b>C 25-21</b><br>Connection kit   | 20,29     |      |
| 87   | шт.<br>pc | <b>C25-100</b><br>Подсоединительный комплект<br>Connection kit           | 25,12     |      |
| 88   | шт.<br>pc | <b>C25-100-METAL</b><br>Connection kit                                   | 62,65     |      |
| 89   |           | <b>C 16-29</b><br>Connection kit   | 13,52     |      |
| 90   | шт.<br>pc | <b>C 16-100</b><br>Connection kit  | 16,77     |      |
| 91   | шт.<br>pc | <b>CE 20-01</b><br>Connection kit with End seal                          | 13,46     |      |
| 92   |           | <b>VIA-CE-01</b><br>Connection and End Seal kit                          | 41,95     |      |
| 93   |           | <b>VIA-L1</b><br>Heat Resistant Cold Lead Cable                          | 13,11     |      |
| 94   |           | <b>E-06</b><br>End Seal  | 12,83     |      |
| 95   |           | <b>E-19</b><br>End Seal  | 26,63     |      |
| 96   |           | <b>E-100-E</b><br>End Seal   | 82,80     |      |
| 97   |           | <b>E-100-L-E</b><br>Lighted End Seal                                     | 208,10    |      |
| 98   |           | <b>E-150</b><br>End Seal   | 44,71     |      |
| 99   |           | <b>C-150-E (Eex e)</b><br>Low profile power connection kit               | 114,68    |      |
| 100  |           | <b>CW-C/S-150-E (Eex e)</b><br>Low profile power connection kit          | 118,68    |      |
| 101  | m         | <b>C-150-PC (3x2,5 mm<sup>2</sup>)</b><br>Silicone insulated power cable | 10,76     |      |
| 102  |           | <b>CS-150-2.5-PI</b><br>Cable Splice Kit                                 | 79,90     |      |
| 103  |           | <b>CS-150-6-PI</b><br>Cable Splice Kit                                   | 149,45    |      |
| 104  |           | <b>CS-150-25-PI</b><br>Cable Splice Kit                                  | 308,15    |      |
| 105  |           | <b>CS-150-UNI-PI</b><br>Cable Splice Kit                                 | 142,28    |      |
| 106  |           | <b>CS-20-2.5-PI-NH</b><br>Cable Splice Kit                               | 114,68    |      |
| 107  |           | <b>JBS-100-E (Eex e)</b><br>Single Entry Junction Box                    | 176,23    |      |
| 108  |           | <b>JBS-100-L-E (Eex e)</b><br>Single Entry Junction Box, Lighted         | 335,48    |      |

Tyco Thermal Controls 2009 .

| Item | Unit | Description  | price USD | Unit |
|------|------|--|-----------|------|
| 109  |      | <b>JBS-100-EP (Eex e)</b><br>Single Entry Junction Box   | 220,80    |      |
| 110  |      | <b>JBS-100-L-EP (Eex e)</b><br>Single Entry Junction Box, Lighted  | 386,40    |      |
| 111  |      | <b>JBM-100-E (Eex e)</b><br>Multiple Entry Junction Box  | 256,96    |      |
| 112  |      | <b>JBM-100-L-E (Eex e)</b><br>Multiple Entry Junction Box, Lighted   | 390,68    |      |
| 113  |      | <b>JBM-100-EP (Eex e)</b><br>Multiple Entry Junction Box   | 290,90    |      |
| 114  |      | <b>JBM-100-L-EP (Eex e)</b><br>Multiple Entry Junction Box, Lighted  | 445,88    |      |
| 115  |      | <b>JBU-100E (Eex e)</b><br>Junction Box  | 133,72    |      |
| 116  |      | <b>JBU-100-L-E (Eex e)</b><br>Junction Box   | 286,63    |      |
| 117  |      | <b>JBU-100-EP (Eex e)</b><br>Junction Box  | 146,56    |      |
| 118  |      | <b>JBU-100-L-EP (Eex e)</b><br>Junction Box  | 326,92    |      |
| 119  |      | <b>JB-EX-20 (EE x e)</b> (1xM25 + 3xM20)<br>1-phase splitterbox (1xM25 + 3xM20), 4 terminals x 10 sq.mm: L1,N,PE-PE        | 131,65    |      |
| 120  |      | <b>JB-EX-21 (EE x e)</b> (1xM32 + 6xM20)<br>3-phase splitterbox (1xM32 + 6xM20), 6 terminals x 10 sq.mm: L1,L2,L3,PE-PE-PE | 168,77    |      |
| 121  |      | <b>JB-82</b><br>Junction Box   | 67,90     |      |
| 122  |      | <b>JB-16-02</b><br>Junction Box  | 24,01     |      |
| 123  |      | <b>T-100 (Eex e)</b><br>Tee connection kit   | 193,20    |      |
| 124  |      | <b>JB-SB-26</b><br>K<br>Junction box Support Bracket   | 34,91     |      |
| 125  |      | <b>SB-100</b><br>c<br>Junction box Support Bracket and Insulation Entry  | 58,65     |      |
| 126  |      | <b>SB-101</b><br>Junction box Support Bracket  | 44,85     |      |
| 127  |      | <b>SB-110</b><br>Junction box Support Bracket  | 29,12     |      |
| 128  |      | <b>SB-111</b><br>Junction box Support Bracket  | 29,95     |      |
| 129  |      | <b>SB-120</b> /<br>Junction box Support Bracket  | 40,30     |      |
| 130  |      | <b>JB-SB-08</b> JB 16-02<br>K<br>Junction box Support Bracket  | 13,25     |      |
| 130  |      | <b>IEK 25-PIPE</b><br>Insulation Entry Kit   | 21,39     |      |
| 131  |      | <b>IEK 25-04</b><br>Insulation Entry Kit   | 16,84     |      |
| 132  |      | <b>IEK 25-05-PC</b><br>Insulation Entry Kit For Power Cable  | 12,42     |      |
| 133  |      | <b>IEK20-PI</b><br>Insulation Entry Kit For Power Cable  | 22,91     |      |
| 134  |      | <b>GL-44-M20-KIT</b> 20<br>Cable Gland M20 with sleeve for earth core  | 16,70     |      |
| 135  |      | <b>GL-45-M32</b> 32<br>Cable Gland M32   | 9,94      |      |
| 136  |      | <b>ETL-R</b> " "<br>Warning labels   | 1,66      |      |
| 137  |      | <b>CW-LAB-EX-KIT</b><br>Circuit identification lable for PI heating cables   | 17,80     |      |
| 138  |      | <b>G-02</b><br>Protective sleeve   | 28,15     |      |
| 139  | m    | <b>GS-54 (16 / .)</b>  | 19,60     |      |

Tyco Thermal Controls 2009 .

| Item | Unit      | Description                                    | price USD | Unit |
|------|-----------|--|-----------|------|
|      | roll      | Rolls of glassfiber adhesive tape              |           |      |
| 140  |           | <b>ATE -180</b>                                | 65,41     |      |
|      | roll      | Rolls of aluminium adhesive tape 50 m          |           |      |
| 141  |           | <b>GT-66 (20 / .)</b>                          | 13,94     |      |
|      | roll      | Rolls of glassfiber adhesive tape              |           |      |
| 142  |           | <b>JBS-SPA (5 . )</b>                          | 34,09     |      |
|      | pack      | Small pipe adapter                             |           |      |
| 143  |           | <b>HARD-SPACER-SS-25MM-25M</b>                 | 114,54    |      |
|      | roll      | Mounting perforated strip 25 m                 |           |      |
| 144  |           | <b>S-21</b>                                    | 38,78     |      |
|      |           | Inline Splice                                  |           |      |
| 145  |           | <b>S-69</b>                                    | 87,22     |      |
|      | шт.<br>pc | Inline Splice                                  |           |      |
| 146  |           | <b>EMK-XS</b>                                  | 38,43     |      |
|      | шт.<br>pc | Inline Splice                                  |           |      |
| 147  |           | <b>S-150</b>                                   | 88,60     |      |
|      | шт.<br>pc | Inline Splice                                  |           |      |
| 148  |           | <b>PSE-047</b>                                 | 3,59      |      |
|      |           | Pipe strap for support brackets                |           |      |
| 149  |           | <b>PSE-090</b>                                 | 4,00      |      |
|      |           | Pipe strap for support brackets                |           |      |
| 150  |           | <b>PSE-280</b>                                 | 6,35      |      |
|      |           | Pipe strap for support brackets                |           |      |
| 151  |           | <b>PSE-540</b>                                 | 12,01     |      |
|      |           | Pipe strap for support brackets                |           |      |
| 152  |           | <b>KBL-09</b>                                  | 18,08     |      |
|      | packs     | Cable Tie for fixing the Heater (100 pcs)      |           |      |
| 153  |           | <b>KBL-10</b>                                  | 36,57     |      |
|      | packs     | Cable Tie for fixing the Heater (100 pcs)      |           |      |
| 154  |           | <b>RAYSTAT EX-02 (EEx d II C)</b>              | 515,15    |      |
|      |           | Control Thermostat                             |           |      |
| 155  |           | <b>GL-33 (EEx d II C)</b>                      | 30,36     |      |
|      |           | 3/4" NPT Cable Gland for armoured power cables |           |      |
| 156  |           | <b>RAYSTAT EX-03 (EEx e m ia III C)</b>        | 949,30    |      |
|      |           | Electronic Control Thermostat                  |           |      |
| 157  |           | <b>RAYSTAT EX-04 (EEx e m ia III C)</b>        | 1 010,57  |      |
|      |           | Ambient Electronic Thermostat                  |           |      |
| 158  |           | <b>T-M-20-S/+70+350C/</b>                      | 1 787,38  |      |
|      |           | Lock Out Thermostat                            |           |      |
| 159  |           | <b>RAYSTAT-CONTROL-10</b>                      | 433,18    |      |
|      |           | Electronic Thermostat with Indicator           |           |      |
| 160  |           | <b>RAYSTAT-ECO-10</b>                          | 433,18    |      |
|      | pc        | Heating system control unit                    |           |      |
| 161  |           | <b>AT-TS-13</b>                                | 220,80    |      |
|      | шт.<br>pc | Control Thermostat -5 +15                      |           |      |
| 162  |           | <b>AT-TS-14</b>                                | 220,80    |      |
|      | шт.<br>pc | Control Thermostat 0 +120                      |           |      |
| 163  |           | <b>TCON-CSD/07/0-100C</b>                      | 231,29    |      |
|      | шт.<br>pc | DIN- Panelmountable controller 0 +100°         |           |      |
| 164  |           | <b>TCON-CSD/07/0-200C</b>                      | 231,29    |      |
|      | шт.<br>pc | DIN- Panelmountable controller 0 +200°         |           |      |
| 165  |           | <b>TCON-CSD/20</b>                             | 231,29    |      |
|      | шт.<br>pc | DIN- Panelmountable electronic controller      |           |      |
| 162  |           | <b>NGC-30</b>                                  | 6 596,54  |      |
|      | pc        | User interface terminal                        |           |      |
| 162  |           | <b>NGC-30-CR</b>                               | 313,95    |      |
|      | pc        | Card rack                                      |           |      |
| 163  |           | <b>NGC-30-CRM</b>                              | 1 761,71  |      |
|      | pc        | Heating system control unit                    |           |      |
| 164  |           | <b>NGC-30-CRMS</b>                             | 1 959,05  |      |
|      | pc        | Heating system control unit                    |           |      |
| 165  |           | <b>NGC-30-CTM</b>                              | 626,11    |      |
|      | pc        | Current measurement module                     |           |      |
| 166  |           | <b>NGC-30-CVM</b>                              | 161,46    |      |
|      | pc        | Voltage module                                 |           |      |
| 163  |           | <b>MONITRACE 200N</b>                          | 4 328,78  |      |
|      | pc        | Heating system control unit                    |           |      |
| 164  |           | <b>MONI-RS485-WIRE (305 m)</b>                 | 11,87     |      |
|      | roll      | Shielded twisted pair network cable            |           |      |
| 165  |           | <b>HTC-915-CONT</b>                            | 1 398,22  |      |
|      | pc        | Universal heat tracing controller              |           |      |
| 166  |           | <b>HTC-915-LIM</b>                             | 714,98    |      |
|      | pc        | Temperature limiter                            |           |      |
| 167  |           | <b>HTC-915-CT</b>                              | 82,80     |      |

Tyco Thermal Controls 2009 .

| Item | Unit | Description  | price USD | Unit |
|------|------|--|-----------|------|
|      | pc   | Load current transformer   |           |      |
| 168  |      | <b>HTC-915-ELCT</b>  | 119,51    |      |
|      | pc   | Earth leakage current transformer                                |           |      |
| 169  |      | <b>MONI-PT100-NH</b>   | 110,54    |      |
|      | pc   | Temperature Sensor For Non-Hazardous Areas                       |           |      |
| 170  |      | <b>MONI-PT100-EXE</b>  | 407,65    |      |
|      | pc   | Temperature Sensor For Hazardous Areas                           |           |      |
| 171  |      | <b>MONI-PT100-4/20MA</b>   | 806,89    |      |
|      | pc   | Temperature Sensor With Transmitter, For Hazardous Areas         |           |      |
| 172  |      | <b>TCONTROL-ISOL-01</b>  | 601,27    |      |
|      | pc   | Galvanically isolated module                                     |           |      |
| 173  |      | <b>MONI-RMM2-E</b> (IP66)  | 1 920,27  |      |
|      | pc   | Remote monitoring module   |           |      |
| 174  |      | <b>MONI-RMM2-EX-E</b> (EEx n)                                    | 2 564,04  |      |
|      | pc   | Remote monitoring module   |           |      |
| 175  |      | <b>MONI-RMC-BASE</b>   | 2 219,87  |      |
|      | pc   | Remote control base unit   |           |      |
| 176  |      | <b>MONI-RMC-2RO</b>  | 222,04    |      |
|      | pc   | Remote control two-channel relay output module                   |           |      |
| 177  |      | <b>MONI-RMC-2DI</b>  | 222,04    |      |
|      | pc   | Discret input module   |           |      |
| 178  |      | <b>MONI-RMC-PS24</b>   | 555,04    |      |
|      | pc   | Remote control 24-Vdc power supply unit                          |           |      |
| 179  |      | <b>TCONTROL-CONT-02</b>  | 487,83    |      |
|      |      | Electronic single point controller                               |           |      |
| 180  |      | <b>VIA-DU-20</b>   | 872,78    |      |
|      |      | Controller with Moisture and Temperature Sensor                  |           |      |
| 181  |      | <b>HWA-WAGO-TSTAT-KIT</b>  | 25,81     |      |
|      | pc   | Kit to connect thermostats to junction boxes                     |           |      |
| 182  |      | <b>GL-34 (EEx d II C)</b> 3/4"                                   | 22,49     |      |
|      |      | 3/4"NPT Cable Gland for non-armoured power cables                |           |      |
| 183  |      | <b>GL-36-M25 (EEx e)</b> 25                                      | 7,31      |      |
|      |      | Cable Gland  |           |      |
| 184  |      | <b>GL-38-M25-METAL (EEx d)</b> 25                                | 32,57     |      |
|      |      | Cable Gland  |           |      |
| 185  |      | <b>ADPT-Pg16/M25 (EEx e)</b> Pg16 ( ) 25 ( )                     | 23,74     |      |
|      |      | Pg16 (female) to M25 (male) adaptor                              |           |      |
| 186  |      | <b>REDUCER-M25/PG16 (EEx e)</b> Pg16 ( ) 25 ( )                  | 23,60     |      |
|      |      | M25 (female) to Pg16 (male) reducer                              |           |      |
| 187  |      | <b>REDUCER-M25/20 - EEx d</b> ( ) 25 ( ) 20 ( )                  | 16,70     |      |
|      |      | M25 (male) to M20 (female) reducer                               |           |      |
| 188  |      | <b>REDUCER-M25/20 - EEx d with locknut</b> ( ) 25 ( ) 20 ( )     | 16,70     |      |
|      |      | M25 (male) to M20 (female) reducer with locknut and fibre washer |           |      |
| 189  |      | <b>REDUCER-M25/20- (EEx e)</b> 20 ( ) 25 ( )                     | 3,59      |      |
|      |      | M25 (male) to M20 (female) reducer                               |           |      |
| 190  |      | <b>REDUCER-M32/25-EEXE</b> ( ) 32 ( ) 25 ( )                     | 20,29     |      |
|      |      | M32 (male) to M25 (female) reducer                               |           |      |
| 191  |      | <b>ADPT- 20/M25 - EEx e</b> ( ) 20 ( ) 25 ( )                    | 24,29     |      |
|      |      | M25 (male) to M25 (female) adaptor                               |           |      |
| 192  |      | <b>HWA-PLUG-M20-EXE-PLASTIC</b> 20                               | 4,28      |      |
|      |      | M20 stopping plug  |           |      |